



GATE VALVE SPECIFICATION <DN300

FOR USE WHEN ORDERING

Valve series no		LNS No (if known)	
Size (DN)			

Wedge Type (Click Box)		Closure (Circle)	
Metal	Resilient	CWC	CWO

Pressure Rating (Click Box)			
PN10	PN16	PN25	Other:

Termination (Click Box)			
Flanged	PE Ended	Spigot End	Socket Connections

Valve Operation (Click Box)			
Cap Top	Handwheel	Bevel Gearbox	Spur Gearbox
Actuator (Please complete actuation specification sheet)			

Maximum unbalanced operating pressure:		Flow rate	
---	--	------------------	--

Flange Drilling (Click Box)	PN10	PN16	PN25	ANSI
------------------------------------	-------------	-------------	-------------	-------------

Coating - Preferred Thickness (Click Box)	250 Microns	300 Microns	Other:
--	--------------------	--------------------	---------------

Datum Levels		Gearbox Operating Conditions	
---------------------	--	-------------------------------------	--

Pipe Orientation (Click Box)		Fluid Details (Click Box)	
Vertical	Horizontal	Water	Sewage

Time to Open:		Close:	
----------------------	--	---------------	--

Other Requirements - Additional Options: e.g Non-rising Stem / Outside Screw & Yoke / Pinned Seats

Documentation (Standard, Special O&M's, Drawing, Test Certification)