



CHECK / RECOIL VALVES SPECIFICATION

FOR USE WHEN ORDERING

Valve series no		LNS No (if known)	
Size (DN)			

Pressure Rating (Click Box)	PN16	PN25
-----------------------------	------	------

Maximum Flow Rate	
-------------------	--

Max Pressure Head		Min Pressure Head	
-------------------	--	-------------------	--

Hinge Pin (Click Box)	Stainless Steel	Stainless Steel A4	Bronze
-----------------------	-----------------	--------------------	--------

Fasteners (Click Box)	Zinc Plated	Stainless Steel A4
-----------------------	-------------	--------------------

Flange Drilling (Click Box)	PN10	PN16	PN25
-----------------------------	------	------	------

ANSI	Table D	Table E	
------	---------	---------	--

Coating - Preferred Thickness (Click Box)			
---	--	--	--

250 Microns	300 Microns	Other:
-------------	-------------	--------

Fluid Details	
---------------	--

Pipe Orientation (Click Box)	Vertical	Horizontal
------------------------------	----------	------------

System Data (Click Box)			
-------------------------	--	--	--

Single Pump	Multi Pump	Other:
-------------	------------	--------

Surge Equipment Fitted (Click Box)	Yes	No
------------------------------------	-----	----

Other Requirements - Additional Options e.g Lever, Weight & Guard / Left/Right Side / Bypass Valve / Proximity Switch etc

Documentation (Standard, Special O&M's, Drawing, Test Certification)
--

Note: if possible to correctly size a recoil valve, please provide a hydraulic / surge analysis of the system.