



SERIES 702 KNIFE GATE VALVE SPECIFICATION

FOR USE WHEN ORDERING

Size (DN)		LNS No (if known)	
-----------	--	-------------------	--

Body Material (Click Box)		Yoke Material (Click Box)	
Ductile Iron	Stainless steel	Mild Steel	Stainless Steel

Closure (Click Box)		Spindle (Click Box)	
CWC	CWO	Rising	Non-rising

Flange Drilling (Click Box)	PN10	PN16	PN25
PN40	PN64	ANSI	Other:

Differential Pressure (Click Box)	PN10	PN16	PN25
PN40	PN64		

Sealing (Click Box)	Viton	Teflon	NBR
EPDM	Silicone	Polyurethane	

Coating - Preferred Thickness (Click Box)	150 Microns	250 Microns	300 Microns	Other:
---	-------------	-------------	-------------	--------

Orientation - Direction of Spindle (Click Box)	Vertical	Angled	Horizontal
--	----------	--------	------------

Valve to be Operated by (Click Box)			
Bare Shaft	Cap Top	Handwheel (May Require Gearbox)	Bevel Gearbox
Spur Gearbox	Lever Operation	Actuator (Please complete actuation specification sheet)	

Actuation (Click Box)	Electric	Pneumatic	Hydraulic
-----------------------	----------	-----------	-----------

Actuator Mounting (Click Box)	F10	F14	F16	F20	F25
-------------------------------	-----	-----	-----	-----	-----

Fluid Details (Click Box)	Water	Sewage
---------------------------	-------	--------

Other Requirements - Additional Options

Documentation (Standard, Special O&M's, Drawing, Test Certification)

Note:

- Flow Rate m/sec: If over 3.5m/s another valve should be considered, please refer to technical support