



AVK FLANGED PIPE

712/5210-001

900 MM, PN 10/16

AVK's range of fittings comprises a wide selection of variants with socket, tyton and flange connection. The fittings are made of ductile iron min. GJS-400 (GGG-40) and are epoxy coated according to DIN 30677-2 and GSK specifications - internally and externally.

Product description:


Double flange pipe type FF for water, waste water and neutral liquids to max. 70° C

Standards:


- Designed according to EN 545
- Standard flange drilling to EN1092-2 (ISO 7005-2), PN 10/16

Features:

- Ductile iron fitting to EN 545.
- Body of min. GJS-400-15 (GGG-40).
- Epoxy coated to DIN 30677-2 and GSK guidelines internally and externally.



Expect... **AVK**


Component list:

1. Fitting	Ductile iron
------------	--------------

Components may be substituted with equivalent or higher class materials without prior notification.

Reference nos. and dimensions:

AVK ref. no.	DN mm	Flange drilling	L mm	Theoretical weight / kg
712-0080-52-101	80	PN10/16	900	19
712-0100-52-101	100	PN10/16	900	23
712-0125-52-101	125	PN10/16	900	29
712-0150-52-101	150	PN10/16	900	35
712-0200-52-100	200	PN10	900	50
712-0200-52-101	200	PN16	900	50
712-0250-52-100	250	PN10	900	67
712-0250-52-101	250	PN16	900	67
712-0300-52-100	300	PN10	900	87
712-0300-52-101	300	PN16	900	87
712-0350-52-100	350	PN10	900	129
712-0350-52-101	350	PN16	900	129
712-0400-52-100	400	PN10	900	160
712-0400-52-101	400	PN16	900	160
712-0450-52-100	450	PN10	900	202
712-0450-52-101	450	PN16	900	202
712-0500-52-100	500	PN10	900	237
712-0500-52-101	500	PN16	900	237
712-0600-52-100	600	PN10	900	329
712-0600-52-101	600	PN16	900	329